First-principles study of $CaB_{12}H_{12}$ as a potential solid-state conductor for Ca

Julius Koettgen,^{a,b} Christopher J. Bartel,^b Jimmy-Xuan Shen,^{a,c} Kristin A. Persson^{a,c} and Gerbrand Ceder^{*a,b}

Calcium dodecahydro-closo-dodecaborate, $CaB_{12}H_{12}$, was calculated to have a percolating Ca migration path with low activation barrier (650 meV). The formation of Ca vacancies required for diffusion was calculated to be thermodynamically feasible by substitution of Ca with Al, Bi, or a number of trivalent rare-earth cations.

Advances in battery technologies are necessary for a growing demand in energy storage due to the use of energy from sustainable but fluctuating sources, the electrification of transport, and the expansion of mobile applications. Calcium batteries are a potential alternative to current polymer Li-ion and future solid-state lithium technology^{1–4} as Ca is more earthabundant than Li, and resources like cobalt and nickel that are viewed critically today concerning availability and sustainability may be potentially avoided.

The search for the optimal materials that might enable Ca batteries is still in the early stages. Ponrouch et al. reported reversible Ca plating and stripping from a traditional liquid carbonate-based electrolyte at elevated temperature, but the Coulombic efficiency was found to be low.5 Wang et al. showed that Ca can be plated and stripped at room temperature.6 Lipson et al. demonstrated reversible Ca intercalation using manganese hexacyanoferrate (MFCN) as a cathode material, a dry nonaqueous liquid electrolyte, and elemental tin as the anode.7 Ca metal would be preferred as the anode, but no electrolyte has yet been shown to reversibly plate and strip Ca metal with high Coulombic efficiency.^{5,8} In this work, we discuss a possible Ca solid-state electrolyte, which promises superior mechanical and thermal stability to liquid electrolytes. However, a solid-state electrolyte requires high Ca mobility to enable sufficient Ca transport at low operating temperatures. Previously discussed candidates for Mg solid-state electrolytes are materials based on <code>closo-borates¹4</code> including B₁₂H₁₂²-, B₁₀H₁₀²-, CB₉H₁₀⁻-, and CB₁₁H₁₂⁻- anions that show high Li and Na conductivities (10¹-1 S cm¹-1).15−23 In fact, <code>closo-borate</code> salts have been intensively discussed for use in liquid electrolytes for Mg and Ca batteries.²4,25

In this work, Ca diffusion in calcium dodecahydro-closo-dodecaborate, $CaB_{12}H_{12}$, is investigated using *ab initio* calculations to assess its potential as a Ca solid-state electrolyte. Density-functional theory (DFT) calculations combined with the nudged elastic band (NEB) method are used to calculate the minimum energy pathways as well as the migration energies for Ca diffusion. $CaB_{12}H_{12}$ was previously synthesized²⁶ and characterized theoretically,²⁷ but has not been previously considered as a potential solid-state Ca conductor. The Li and Na analogs, $Li_2B_{12}H_{12}$, and $Na_2B_{12}H_{12}$, show high ion mobility with low migration barriers of about 0.2 eV in calculations (Li, Na) and 0.45 eV experiments (Li).²³ Here, we show that the percolating Ca migration path has a calculated activation barrier of 0.65 eV by a vacancy-mediated diffusion mechanism.

The crystal structure of $CaB_{12}H_{12}$ is shown in Fig. 1. Ca^{2+} ions are surrounded by five icosahedral $[B_{12}H_{12}]^{2-}$ anions and interact with eight neighboring H atoms. 26 Three of the $[B_{12}H_{12}]^{2-}$ anions form a triangular equatorial plane that is centered on each Ca^{2+} ion. Two of the $[B_{12}H_{12}]^{2-}$ anions are in axial position. In $CaB_{12}H_{12}$, there are five geometrically unique Ca migration paths with a migration path length less than 9 Å (Fig. 1). Three Ca migration paths connect Ca sites that are in different layers

Electronic Supplementary Information (ESI) available.

For example, for Li and Mg solid-state electrolytes, migration barriers as low as 250 and 370 meV have been reported, respectively, $^{9-11}$ and similar migration barriers are required for Ca solid-state electrolytes. However, few materials with low Ca migration barriers and low electronic conductivity are known. $\beta^{\prime\prime}$ -alumina may be one of the few materials that has been considered as a high-temperature Ca solid-state electrolyte with an experimental activation energy for Ca conduction of 570 meV 12 but has been mostly considered for high-temperature batteries. 13

^{a.} Materials Sciences Division, Lawrence Berkeley National Laboratory, Berkeley, CA 94720, USA. E-mail: gceder@berkeley.edu

b. Department of Materials Science and Engineering, University of California, Berkeley, CA 94720, USA

^{c.} Energy Technologies Area, Lawrence Berkeley National Laboratory, Berkeley, CA, USA

of the $\mathsf{B}_{12}\mathsf{H}_{12}\text{-cages}.$ Two Ca migration paths connect Ca sites that are in the same layer of the $B_{12}H_{12}$ -cages. Our calculations show that migration between the layers occurs with a smaller activation barrier than migration in the layers. Fig. 2 shows the calculated energies relative to the initial state along the migration paths. In the B₁₂H₁₂ layers, Ca migration barriers vary between 1300-1400 meV. Between the B₁₂H₁₂ layers, Ca migration barriers vary between 640-740 meV with a percolating path having a barrier as low as 650 meV. The latter is to our knowledge one of the lowest reported Ca migration barriers reported for a Ca solid-state electrolyte. Few Ca migration barriers in discharged Ca cathodes (Ca-intercalated materials) have been reported to have lower migration barriers including the hypothetical spinel CaCr₂O₄ (610 meV).²⁸ These materials may be ineligible as solid-state electrolytes due to potential electronic conductivity while for CaB₁₂H₁₂ a negligible electronic conductivity is expected due to the calculated band gap larger than 4 eV.




Fig. 1: $CaB_{12}H_{12}$ structure and possible migration paths. Ca is shown as pink spheres, B as green spheres, and H as grey spheres. Possible migration paths below 9 Å are shown as lines between Ca positions. (a) Paths between layers have lower migration barriers than (b) paths in between layers.

The low barriers in closo-borates have been previously attributed to three energy frustration phenomena discussed in detail for Li₂B₁₂H₁₂ and Na₂B₁₂H₁₂ by Kweon et al.²³ Firstly, the high density of accessible interstitial sites leads to several sites of similar energy (frustration of sites). Secondly, cations prefer to dock to specific anion sites, which differ from the sites that lead to a higher preferred symmetry, leading to a local bond frustration. Thirdly, anion reorientations are facile and lead together with other low-frequency thermal vibrations to fluctuations in the local potential ('dynamic frustrations'). These frustrations lead to a flat energy landscape and facile cation migration. 23 As the structure of $CaB_{12}H_{12}$ is very similar to the investigated structures ($Li_2B_{12}H_{12}$ and $Na_2B_{12}H_{12}$), we assume that these observations are also true for CaB₁₂H₁₂, for which we also show a relatively flat energy landscape in this work (see Fig. 2).




Fig. 2: $CaB_{12}H_{12}$ migration paths. The energy relative to the initial state is shown as a function of the normalized reaction coordinate. Lines are a guide to the eye only.

To understand why migration within layers occurs with considerably higher barriers (1300-1400 meV) than between layers (640-740 meV), we investigated several geometric parameters of the two groups of paths. Migration path lengths, coordination environments, bond lengths, polyhedral volumes, and the number of $B_{12}H_{12}$ cages adjacent to the migration path are provided in Table 1 for the migration paths shown in Fig. 1. Ca-H bonds with length, r, < 2.7 Å around the mobile Ca in the transition state are considered. Additionally, the effective coordination number according to Hoppe²⁹ is included. Surprisingly, all of these parameters are similar in both migration path groups despite the migration barriers differing by \sim 600 meV.

Table 1: Geometric parameters of the migration paths. Migration path lengths, coordination environments, 29 bond lengths, polyhedral volumes, and the number of $\rm B_{12}H_{12}$ cages that are adjacent to the migration path are given. Ca-H bonds with length, $r,<2.7~\rm \mathring{A}$ around the mobile Ca in the transition state are considered.

	Migration path	Migration path
	between layers	within the layers
Migration barrier	0.64 – 0.74 eV	1.30 – 1.40 eV
Path length	6.8–7.0 Å	6.9–7.2 Å
Coordination	6–7	6
Eff. coordination	6.2, 5.5, 6.0	5.5, 5.5
Ca-H bonds	2.3–2.4 Å	2.3 Å
Polyhedral volume	16-20 Å ³	16 ų
Between B ₁₂ H ₁₂	2–4	2

As the geometry of the investigated paths is unable to distinguish between the high and low energy paths, we also investigated the charge density along all paths. To quantify the amount of charge "seen" by the migrating Ca ion, we integrated the valence electron density in a cylinder with a radius of 0.4 Å that spans between the final and initial site of the migrating Ca. The latter is a new in-house developed method that might provide insights for understanding migration paths in the future. All electron densities were integrated for the Ca-free $B_{12}H_{12}$ framework. Table 2 shows the Ca migration paths lengths, barriers, and their charge density along the path. Fig. 3 and Fig. S1 (see ESI) show the charge density along all Ca migration paths.

Table 2: Ca migration paths lengths, barriers, and their charge density along the path. The charge density is lower in paths between layers

Path	Migration	Migration	Valence elec-
relative to	path length	barrier	trons along path
layers	[Å]	[eV]	[e]
between	6.80	0.64	0.12
between	6.85	0.74	0.20
between	6.96	0.65	0.24
in	6.94	1.30	0.68
in	7.15	1.40	0.49




Fig. 3: Charge density of $B_{12}H_{12}$ along all Ca migration paths. Ca positions (pink spheres) are shown in reference to $CaB_{12}H_{12}$. Paths are colored according to the legend in Fig. 1. Fig. a) shows the (-1.55|1.55|1) plane that is a distance of 0.73 Å distance from the origin; b) is the (1|1|0) plane with 7.37 Å distance from the origin; and c) is the (0|0|1) plane with 9.38 Å distance from the origin as visualized in Fig. S1 (see ESI).

For migration paths between layers, the charge density encountered by the Ca ion is below 0.25 e. For migration paths in the layers, the charge density is 0.49 e or above and, therefore, twice as large. This suggests that Ca needs to move through more charge for migration within the layers than between the layers. The core electrons of Ca²⁺ cannot overlap with the charge density in the structure (Pauli exclusion principle) and must displace the charge density during migration. As a result, an increase in charge encountered along the migration path is counterproductive for migration, indicating why migration between the layers occurs with a smaller activation barrier.

High Ca conductivity requires both low percolating migration barriers as well as a sufficient concentration of Ca vacancies ($V_{Ca}^{\prime\prime}$). Therefore, Ca vacancies need to be created in CaB₁₂H₁₂. In this work, three ways to create Ca vacancies are investigated: extraction of CaH₂, doping of the B³⁺ sites with C⁴⁺, and doping of the Ca²⁺ sites with a number of higher valent (3+ or 4+) species.

The extraction of CaH₂ creates one Ca and two H vacancies. This concept was experimentally demonstrated by extracting LiH from Li₂B₁₂H₁₂ using high energy ball milling to form Li_{1.92}B₁₂H_{11.69}. ³⁰ The LiH extraction led to a lattice expansion verified by X-ray diffraction, and Raman experiments showed a local distortion of the B-H bonding. As a result of the Li vacancies created, the conductivity increased by a factor of 1000 according to impedance spectroscopy measurements. Kim *et al.* calculated the extraction of 2% Li (Li₆₄B₃₈₄H₃₈₄ \rightarrow Li₆₃B₃₈₄H₃₈₃ + LiH) to have a Gibbs free energy of 70 kJ/mol. ³⁰ In this work, we

calculated that 6% Ca extraction ($Ca_{16}B_{192}H_{192} \rightarrow Ca_{15}B_{192}H_{190} + CaH_2$) is highly endothermic, with a reaction enthalpy of 821 kJ/mol (8.50 eV/V $_{Ca}^{\prime\prime}$). Although this approach was used successfully for Li extraction from Li₂B₁₂H₁₂, these calculations suggest CaH₂ cannot be readily extracted from CaB₁₂H₁₂.

A second way to create Ca vacancies is doping of the B³+ sites with C⁴+, which creates one Ca vacancy per two C dopants. However, the reaction enthalpy for this substitution (Ca₁₆B₁₉₂H₁₉₂ + 2 C \rightarrow Ca₁₅B₁₉₀C₂H₁₉₂ + 0.5 Ca + 0.5 CaB₄) is highly unfavorable (585 kJ/mol, 6.06 eV/V $^{\prime\prime}_{Ca}$), even in the presence of oxygen (Ca₁₆B₁₉₂H₁₉₂ + 2 C + 0.25 O2 \rightarrow Ca₁₅B₁₉₀C₂H₁₉₂ + 0.5 CaB₄ + 0.5 CaO, 273 kJ/mol, 2.83 eV/V $^{\prime\prime}_{Ca}$), and therefore not practical.




Fig. 4: Energy per Ca vacancy for the structure $Ca_{13}M_2B_{192}H_{192}$ where each candidate dopant ion, M, is shown in green (stable dopant) or red (unstable dopant). Doping $CaB_{12}H_{12}$ with Al, Bi, and rare-earth elements is energetically favorable.

A third way to create Ca vacancies is doping of the Ca2+ sites with a higher valent species such as Al3+ or rare-earth ions, RE3+. Similar to doping with C4+, one Ca vacancy is created per two M³+ dopants. In order to investigate if the substitution of one Ca with a higher valent species M3+ (Ca13M2B192H192) leads to a stable compound, we calculated the driving force for the decomposition of the doped compound into the lowest energy set of competing compounds. A stable compound has no driving force to separate into a combination of the most stable compounds in its corresponding chemical system,31 which we determine here using the Materials Project.³² The driving force for decomposition is calculated as the formation energy of the compound against the convex hull of ground-state energies in the relevant portion of the phase diagram ('energy above the hull per atom', E_{hull}). 33,34 Stable compounds have E_{hull} < 0. In Fig. 4, we show the energy per Ca vacancy ($E_{hull} \times 399$) for a number of Ca₁₃M₂B₁₉₂H₁₉₂ compounds. Elements highlighted in green indicate stable substitutions of a higher valent species for Ca, suggesting they can be used to create Ca vacancies in CaB₁₂H₁₂. E_{hull} < 0 provides the equilibrium reaction energy from the neighboring stable entries (inverse distance to the hull). Therefore, doping with aluminum, bismuth, or any of the rareearth cations is shown to be the most promising way to create Ca vacancies. However, placing a non-mobile ion on the Ca site may also decrease the mobility of Ca. Therefore, a balance between vacancy creation and retention of percolating Ca diffusion pathways is required to optimize the conductivity.

We investigated the mobility of Ca in dodecahydro-closo-dodecaborate $CaB_{12}H_{12}$ based on the high mobility of Na and Li in a similar framework. We find that the lowest barrier percolating pathway has a calculated barrier of only 650 meV,

which is one of the lowest reported solid-state migration barriers for Ca. Our analysis indicates that the integrated electron density along the path qualitatively correlates with the barrier with a lower electron density leading to a lower barrier. This suggests that the core repulsion of Ca2+ with the host's electron density is the prime factor dictating the migration barrier. Our calculations show that doping Ca sites with Al, Bi, or rare-earth elements is a potential low energy way to create the Ca vacancies required to activate the vacancy-mediated diffusion mechanism studied in this work. Although 650 meV is a low barrier for Ca²⁺, it is still a relatively high barrier for a solid electrolyte, indicating that CaB₁₂H₁₂ can probably only be used at high temperature. Possible avenues for improving conductivity are doping with tetravalent ions that decrease migration barriers in their neighborhood or introducing disorder as discussed for $Na_2(B_{12}H_{12})0.5(B_{10}H_{10})_{0.5}$.35

J.K. and J.X.S were supported by the Volkswagen group. Phase stability work and doping analysis (CB) were supported by the Joint Center for Energy Storage Research (JCESR). This research used resources of the National Energy Research Scientific Computing Center (NERSC), a U.S. Department of Energy Office of Science User Facility operated under Contract No. DE-ACO2-05CH11231. This work used the Extreme Science and Engineering Discovery Environment (XSEDE), which is supported by National Science Foundation grant number ACI-1548562.³⁶

Conflicts of interest

This work was supported financially by the Volkswagen group.

Notes and references

- J. Muldoon, C. B. Bucur and T. Gregory, Chem Rev, 2014, 114, 11683–11720.
- N. Kamaya, K. Homma, Y. Yamakawa, M. Hirayama, R. Kanno, M. Yonemura, T. Kamiyama, Y. Kato, S. Hama, K. Kawamoto and A. Mitsui, *Nat. Mater.*, 2011, 10, 682–686.
- 3 Y. Seino, T. Ota, K. Takada, A. Hayashi and M. Tatsumisago, Energy Environ. Sci., 2014, 7, 627–631.
- 4 T. Famprikis, P. Canepa, J. A. Dawson, M. S. Islam and C. Masquelier, *Nat. Mater.*, 2019, 18, 1278–1291.
- A. Ponrouch, C. Frontera, F. Bardé and M. R. Palacín, *Nat. Mater.*, 2016, 15, 169–172.
- 6 D. Wang, X. Gao, Y. Chen, L. Jin, C. Kuss and P. G. Bruce, *Nat Mater*, 2018, **17**, 16–20.
- 7 A. L. Lipson, B. Pan, S. H. Lapidus, C. Liao, J. T. Vaughey and B. J. Ingram, *Chem. Mater.*, 2015, **27**, 8442–8447.
- D. Aurbach, R. Skaletsky and Y. Gofer, J. Electrochem. Soc., 1991, 138, 3536–3545.
- 9 P. Canepa, S.-H. Bo, G. Sai Gautam, B. Key, W. D. Richards, T. Shi, Y. Tian, Y. Wang, J. Li and G. Ceder, *Nat Commun*, 2017, 8, 1759.
- 10 R. Xu, Z. Wu, S. Zhang, X. Wang, Y. Xia, X. Xia, X. Huang and J. Tu, *Chem. Eur. J.*, 2017, **23**, 13950–13956.
- 11 J. Koettgen, C. J. Bartel and G. Ceder, *Chem Commun*, 2020, **56**, 1952–1955.
- 12 J. Ni, T. T. Tsai and D. H. Whitmore, *Solid State Ion.*, 1981, **5**, 199–
- 13 A. F. Sammells and B. Schumacher, *J Electrochem Soc*, 1986, **133**, 235–236.

- 14 S. Fisher, A. Tomich, S. Lovera, J. Kleinsasser, J. Guo, M. Asay, H. Nelson and V. Lavallo, Chem. Rev., 2019, 119, 8262–8290.
- 15 R. Mohtadi and S. Orimo, *Nat. Rev. Mater.*, 2017, **2**, 16091.
- 16 T. J. Udovic, M. Matsuo, A. Unemoto, N. Verdal, V. Stavila, A. V. Skripov, J. J. Rush, H. Takamura and S. Orimo, *Chem Commun*, 2014, **50**, 3750–3752.
- 17 W. S. Tang, A. Unemoto, W. Zhou, V. Stavila, M. Matsuo, H. Wu, S. Orimo and T. J. Udovic, *Energy Environ. Sci.*, 2015, 8, 3637–3645.
- 18 W. S. Tang, K. Yoshida, A. V. Soloninin, R. V. Skoryunov, O. A. Babanova, A. V. Skripov, M. Dimitrievska, V. Stavila, S. Orimo and T. J. Udovic, ACS Energy Lett., 2016, 1, 659–664.
- 19 W. S. Tang, M. Matsuo, H. Wu, V. Stavila, W. Zhou, A. A. Talin, A. V. Soloninin, R. V. Skoryunov, O. A. Babanova, A. V. Skripov and others, Adv. Energy Mater., 2016, 6, 1502237.
- 20 A. V. Skripov, R. V. Skoryunov, A. V. Soloninin, O. A. Babanova, W. S. Tang, V. Stavila and T. J. Udovic, *J. Phys. Chem. C*, 2015, **119**, 26912–26918.
- 21 T. J. Udovic, M. Matsuo, W. S. Tang, H. Wu, V. Stavila, A. V. Soloninin, R. V. Skoryunov, O. A. Babanova, A. V. Skripov, J. J. Rush, A. Unemoto, H. Takamura and S. Orimo, *Adv. Mater.*, 2014, 26, 7622–7626.
- 22 N. Verdal, T. J. Udovic, V. Stavila, W. S. Tang, J. J. Rush and A. V. Skripov, *J. Phys. Chem. C*, 2014, **118**, 17483–17489.
- 23 K. E. Kweon, J. B. Varley, P. Shea, N. Adelstein, P. Mehta, T. W. Heo, T. J. Udovic, V. Stavila and B. C. Wood, *Chem. Mater.*, 2017, 29, 9142–9153.
- 24 T. J. Carter, R. Mohtadi, T. S. Arthur, F. Mizuno, R. Zhang, S. Shirai and J. W. Kampf, *Angew. Chem. Int. Ed.*, 2014, **53**, 3173–3177.
- 25 M. N. Guzik, R. Mohtadi and S. Sartori, J. Mater. Res., 2019, 34, 877–904.
- 26 V. Stavila, J.-H. Her, W. Zhou, S.-J. Hwang, C. Kim, L. A. M. Ottley and T. J. Udovic, *J. Solid State Chem.*, 2010, **183**, 1133–1140.
- 27 A. D. Kulkarni, L.-L. Wang, D. D. Johnson, D. S. Sholl and J. K. Johnson, *J. Phys. Chem. C*, 2010, **114**, 14601–14605.
- 28 M. Liu, Z. Rong, R. Malik, P. Canepa, A. Jain, G. Ceder and K. A. Persson, *Energy Env. Sci*, 2015, 8, 964–974.
- 29 R. Hoppe, Z. Für Krist.-Cryst. Mater., 1979, 150, 23–52.
- S. Kim, N. Toyama, H. Oguchi, T. Sato, S. Takagi, T. Ikeshoji and S. Orimo, *Chem. Mater.*, 2018, **30**, 386–391.
- 31 Z. Rong, R. Malik, P. Canepa, G. Sai Gautam, M. Liu, A. Jain, K. Persson and G. Ceder, *Chem Mater*, 2015, **27**, 6016–6021.
- 32 A. Jain, S. P. Ong, G. Hautier, W. Chen, W. D. Richards, S. Dacek, S. Cholia, D. Gunter, D. Skinner, G. Ceder and K. A. Persson, APL Mater., 2013, 1, 011002.
- 33 M. Liu, A. Jain, Z. Rong, X. Qu, P. Canepa, R. Malik, G. Ceder and K. A. Persson, *Energy Environ. Sci.*, 2016, **9**, 3201–3209.
- 34 S. P. Ong, L. Wang, B. Kang and G. Ceder, *Chem. Mater.*, 2008, **20**, 1798–1807.
- 35 L. Duchêne, S. Lunghammer, T. Burankova, W.-C. Liao, J. P. Embs, C. Copéret, H. M. R. Wilkening, A. Remhof, H. Hagemann and C. Battaglia, *Chem. Mater.*, 2019, 31, 3449–3460.
- 36 J. Towns, T. Cockerill, M. Dahan, I. Foster, K. Gaither, A. Grimshaw, V. Hazlewood, S. Lathrop, D. Lifka, G. D. Peterson, R. Roskies, J. R. Scott and N. Wilkins-Diehr, *Comput. Sci. Eng.*, 2014, 16, 62–74.