1 **MeteoMex: Open infrastructure for** 2 **networked environmental monitoring and** 3 **agriculture 4.0**

4 **Robert Winkler¹**

5 ¹**CINVESTAV Unidad Irapuato, Department of Biochemistry and Biotechnology, Km. 9.6**
6 **Libramiento Norte Carr. Irapuato-Len, 36824 Irapuato Gto., Mexico, Katurabi S.A. de**
7 **C.V., 36613 Irapuato Gto., Mexico**

8 Corresponding author:

9 Robert Winkler¹

10 Email address: robert.winkler@cinvestav.mx

11 **ABSTRACT**

12 Air, water, and soil are essential for terrestrial life, but pollution, overexploitation, and climate change
13 jeopardize the availability of these primary resources. Thus, assuring human health and food production
14 requires efficient strategies and technologies for environmental protection. Knowing key parameters such as
15 soil moisture, air, and water quality is essential for smart farming and urban development. The MeteoMex
16 project aims to build simple hardware kits and their integration into current Internet-of-Things (IoT) plat-
17 forms. This paper shows the use of low-end Wemos D1 mini boards to connect environmental sensors
18 to the open-source platform ThingsBoard. Two printed circuit boards (PCB) were designed for mounting
19 components. Analog, digital and I²C sensors are supported. The Wemos ESP8266 microchip provides
20 WiFi capability and can be programmed with the Arduino IDE. Application examples for the MeteoMex
21 aera and terra kits demonstrate their functionality for air quality, soil, and climate monitoring. Further, a
22 prototype for monitoring wastewater treatment is shown, which exemplifies the capabilities of the Wemos
23 board for signal processing. The data are stored in a PostgreSQL database, which enables data mining.
24 The MeteoMex IoT system is highly scalable and of low cost, which makes it suitable for deployment in
25 agriculture 4.0, industries, and public areas. Circuit drawings, PCB layouts, and code examples are free to
26 download from <https://github.com/robert-winkler/MeteoMex>.

27 **Keywords:** Climate change, pollution, air quality, volatile organic compounds, wastewater, smart cities,
28 agriculture 4.0, internet-of-things, Arduino, open hardware

1 INTRODUCTION

The overuse of natural resources by humans and climate change have severe effects on the environment. As a consequence, the global food security is threatened, and pollution-related diseases such as allergies and asthma increase (Vermeulen et al., 2012; Wheeler and Braun, 2013; D'Amato et al., 2015; Lake Iain R. et al., 2017; Cohen et al., 2017; D'Odorico et al., 2018; Dell'Angelo et al., 2018; Patella et al., 2018).

In arid and semi-arid regions, irrigation is essential for agriculture. However, excess watering negatively affects food yield and quality (El-Ansary, 2017; King et al., 2020) and leads to unnecessary consumption of water and energy. Besides, salt accumulation in the soil reduces future yields (Shrivastava and Kumar, 2015; Hutchinson, 2019). The use of treated wastewater is possible for saving drinking water, but wastewater treatment requires energy for pumping and aeration and needs to be optimized (Vergine et al., 2017; Miller-Robbie et al., 2017). Using greenhouses increases the productivity and quality in agriculture because lighting, ventilation, temperature, and watering can be adjusted to the cultivars and external conditions (Jat et al., 2020).

A very efficient strategy to increase food availability is the protection of harvested products against insect infestation and spoilage. In tropical areas, losses of more than half of stored maize grains due to insect pests are possible. Adapted plant genotypes, agrochemicals can minimize those, and improved storage strategies (López-Castillo et al., 2018). Hermetically closed metal containers efficiently reduce insect-related postharvest losses (García-Lara et al., 2007; Tefera et al., 2011). Besides, adequate storage conditions, i.e., light, temperature, and humidity, prolong the shelf-life of human and animal food (Bradford et al., 2018). Some perishable food products require cooling during the complete production and distribution chain (Mercier et al., 2017). Cooling facilities - such as air conditioning, refrigerated trucks, fridges, and freezers - are primary drivers of industrial and domestic energy consumption, though (She et al., 2018).

Air temperature, relative humidity, and barometric pressure are main physical parameters for assessing weather and climate, and have direct effects on human health, ecology and agriculture (Fagerlund et al., 2019; Villalobos et al., 2016; Yu et al., 2018; Adejuwon and Agundiminegha, 2019). Novel machine/deep learning algorithms for developing predictive weather and climate models rely on massive global datasets (Dueben and Bauer, 2018; Scher, 2018; Racah et al., 2017). On the other hand, local meteorological information is essential for evaluating microclimates and for optimizing farming (Shock et al., 2016; Luwesi et al., 2017). Air temperature and humidity also influence the emission of volatile organic compounds (VOC) from factories and building materials and the perceived indoor air quality (Haghighat and De Bellis, 1998; Wolkoff, 1998; Fang et al., 1999; Milota and Lavery, 2003; Fechter et al., 2006; Wolkoff and Kjærgaard, 2007; Liu et al., 2014).

65 *Smart farming* uses soil data such as structure, composition, moisture, salinity, cation ex-
66 change capacity (CEC), and pH to optimize production (Corwin et al., 2003; Grisso et al., 2005;
67 Ould Ahmed et al., 2010). Gathering highly localized data is crucial for the precise control of
68 ideal plant growth conditions. Therefore, a well-equipped greenhouse could contain hundreds
69 of sensors that are connected to a central control unit (Chaudhary et al., 2011).

70 Industrial farming already uses Internet-of-Things (IoT) systems for increasing productivity
71 and efficiency. The European Union supports the development of IoT technology for the agricul-
72 tural and food sector with the project *Internet of Food and Farm 2020* (<https://www.iof2020.eu>).
73 However, for small stakeholders in developing countries, such commercial *agriculture 4.0* tech-
74 nology is usually out-of-reach, despite its tremendous potential in environmental protection
75 and food production, especially in vulnerable regions (Antony et al., 2020; Luthra et al., 2018).
76 Further, most industry-grade IoT systems are built on proprietary hardware and software and
77 require specialists for their operation and adaptations.

78 Initiatives such as the *Public Lab* (<https://publiclab.org>) and *Lab On The Cheap* (<https://www.labonthecheap.com>) (Gibney, 2016), in contrast, promote the community-driven devel-
79 opment of open technology. Such low-cost and *do-it-yourself* (DIY) devices are not only suit-
80 able for *crowd-sourcing* data in so-called *citizen science* (Dickinson et al., 2012), but also state-
81 of-the-art research in the instrumental analysis (Martínez-Jarquín et al., 2016; Rosas-Román
82 et al., 2020). Environmental sensing projects often use simple microcontroller boards such as
83 Arduino (<https://www.arduino.cc>) and Wemos (<https://www.wemos.cc>) variants. The *Cave*
84 *Pearl Data Logger* demonstrates that such devices can operate under harsh conditions (underwa-
85 ter) for more than one year on $3 \times$ A.A. battery power (Beddows and Mallon, 2018). The *Solar*
86 *Powered WiFi Weather Station v 2.0* ([https://www.instructables.com/id/Solar-Powered-](https://www.instructables.com/id/Solar-Powered-WiFi-Weather-Station-V20/)
87 [WiFi-Weather-Station-V20/](https://www.instructables.com/id/Solar-Powered-WiFi-Weather-Station-V20/)) uses a Wemos board and connects wirelessly to Blynk (<https://blynk.io>),
88 ThingSpeak (<https://thingspeak.com>), or an IoT MQTT (<https://mqtt.org>)
89 broker. Many of such excellent community projects on environmental monitoring have been
90 reported. However, reproducing DIY devices requires technical skills, and integrating the sen-
91 sors into a professional IoT framework is too challenging for end-users.

92 The MeteoMex project (<http://www.meteomex.com>) provides an open IoT infrastructure for
93 environmental monitoring, which is scalable, flexible, and suitable for non-experts.
94

Figure 1. MeteoMex aerie A) circuit and B) PCB. The shield connects two sensors using the I²C bus: An BME280 sensor board for measuring temperature, relative humidity, and a CCS811 sensor board for total volatile organic compounds (VOC). Closing jumper J1 is required for using *DeepSleep/WakeUp*.

2 METHODS

2.1 Microcontroller board, circuit, and PCB design

For connecting sensors to wireless networks, Arduino-compatible, single-board microcomputers are used. The low-end Wemos D1 mini board is based on the ESP-8266EX chip (80 MHz, 4 Mb flash memory) and provides WiFi. The board measures $34.2 \times 25.6 \text{ mm}^2$ and weighs 3 g. With a micro-USB connection, the Wemos D1 can be powered and programmed (<https://www.wemos.cc/>). The board features 11 digital input/output pins and one analog input (3.2 V max.). The price of a standard Wemos D1 mini board is approximately 5 USD.

For mounting sensors and other electronic components, printed circuit boards (PCB) were designed that can be stacked on the Wemos boards - so-called *shields*.

The open-source software Fritzing (<https://fritzing.org>) was used for designing the circuits and printed circuit boards (PCB) (Monk, 2015). For fabrication, the PCB layouts were exported to the Gerber file format (<https://www.ucamco.com/en/gerber>). PCB figures in this article were produced with a Gerber file viewer (<https://www.pcbgogo.com/GerberViewer.html>). ALLPCB, China <https://www.allpcb.com/> produced testing lots of 100 pieces each.

The editable Fritzing files and example programs are available from the MeteoMex GitHub repository <https://github.com/robert-winkler/MeteoMex>.

The configuration of the different shields is explained in the following subsections.

Figure 2. MeteoMex terra A) circuit and B) PCB. The connection of one analog soil moisture and one digital DS18B20 temperature sensor is possible. A 10 kΩ pull-up resistor is necessary for temperature measurement. The jumper *J1* is used for programming *DeepSleep/WakeUp*.

2.1.1 MeteoMex aerie

The MeteoMex aerie (Fig. 1) shield uses a Bosch BME280 chip (<https://www.bosch-sensortec.com/products/environmental-sensors/humidity-sensors-bme280/>) to monitor the ambient air parameters temperature, relative humidity, and barometric pressure.

An additional CCS811 sensor (<https://www.sciosense.com/products/environmental-sensors/ccs811-gas-sensor-solution/>), permits the detection of total volatile organic compounds (VOC). Both chips use the I²C bus for sensor data transfer. If the board is powered by batteries, programming a *DeepSleep* mode is recommendable for reducing the energy consumption in idle mode. For waking up the Wemos D1 mini, the jumper *J1* must be closed.

2.1.2 MeteoMex terra

The MeteoMex terra (Fig. 2) shield is designed to connect an analog sensor, such as a conductive or capacitive soil moisture sensor, and a digital DS18B20 temperature sensor. For operating the DS18B20 sensor, a pull-up resistor of 10 kΩ (*R1*) is required.

The power supply of the analog and digital sensor is connected to the pins D1 and D3, respectively. However, some analog sensors require a connection to the 5V pin for reliable operation. This board as well provides a *J1* option.

2.1.3 MeteoMex WasteWater prototype

The MeteoMex WasteWater (Fig. 3) configuration is a slight variation of the terra circuit. An analog Arduino turbidity sensor is used for measuring total suspended solids (TSS). For determining tank filling levels, a Jsn-sr04t waterproof ultrasonic sensor is connected. Both sensors operate on 5 V. For this custom design, no PCB was printed, but the circuit was built on a Perf-board.

All boards were designed for the use of through-hole electronic components for facilitating

Figure 3. MeteoMex WasteWater prototype circuit. The ultrasonic SR04 sensor and the analog sensor for total suspended solids (TSS) both require a 5 V power supply.

136 manual assembly and soldering.

137 **2.2 Programming and Internet-of-Things (IoT) infrastructure**

138 An overview of the IoT infrastructure is shown in **Figure 5**. The programming was done on Win-
139 dows 10 and standard Linux distributions (Fedora and Ubuntu). The IoT platform is running
140 on a Virtual-Private-Server, hosted by IONOS (<https://www.ionos.de>). The operating system
141 of the IoT server is Ubuntu 18.04 LTS (<https://ubuntu.com>).

142 **2.2.1 Programming the Wemos board**

143 The Wemos boards are Arduino-compatible and can be programmed with the open-source and
144 cross-platform software Arduino IDE (<https://www.arduino.cc/en/Main/Software>), using
145 the additional ESP32 board definitions from [https://dl.espressif.com/dl/package_esp32_](https://dl.espressif.com/dl/package_esp32_index.json)
146 [index.json](https://dl.espressif.com/dl/package_esp32_index.json). Compiled programs were transferred to the Wemos boards using a USB interface.
147 For testing and debugging, a serial monitor window was used.

148 **2.2.2 Internet-of-things platform and database**

149 For registration and administration of devices, collecting telemetry data, and visualization, the
150 *Community Edition* of the open-source IoT Platform ThingsBoard (<https://thingsboard.io>)
151 was used.

152 All device and telemetry data are stored in a PostgreSQL database [https://www.postgresql.](https://www.postgresql.org)
153 [org](https://www.postgresql.org). For database queries and administration, the Adminer (<https://www.adminer.org>) database
154 management web interface was installed. Regular maintenance tasks are performed with SQL
155 scripts and server CRON jobs.

2.3 Housing and power supply

MeteoMex kits provide no housing by default, which saves costs and reduces unnecessary plastics waste. The circuits operate at low voltages (5 V), why the devices are safe for humans and animals. For indoor air monitoring, the devices can be simply connected to a USB power supply (Fig. 4 A). For outdoor conditions, the protection against dust, insects, and water might be necessary (Fig. 4 B-E). However, re-used plastic beakers, e.g., from dairy products, usually fulfill this purpose.

Alternatively, to USB port power, the devices can be operated with $3 \times$ A.A. rechargeable batteries or with solar panels and a power bank. Programming a *DeepSleep/WakeUp* routine, a MeteoMex aeria device with BME280 sensor works about three months with $3 \times$ A.A. rechargeable batteries. However, additional electronic components and accumulators have a negative impact on the system's environmental footprint.

The building of the device and housing shown in Figure 4 E is described in an Instructable (<https://www.instructables.com/member/RobertWinkler/instructables/>).

2.4 Availability of MeteoMex kits and code

Additional documentation for building and programming the devices and kits are available from the MeteoMex project page <http://www.meteomex.com>. PCB Fritzing layouts and code examples are deposited at the GitHub repository (<https://github.com/robert-winkler/MeteoMex>) with open license terms.

Figure 4. Different housing and power supply options: A) No housing and direct powering with USB charger, B) 3 × AA rechargeable batteries in commercial enclosure, C) Solar panel and lithium battery with wet room installation box, D) and E) Re-use of plastic beakers.

Figure 5. Scheme of the MeteoMex IoT infrastructure. The devices and the IoT server are located on different continents. Clip-arts from <https://search.creativecommons.org>, Free Clip Art, and SVG Silh.

3 RESULTS AND DISCUSSION

3.1 Internet-of-Things integration of MeteoMex units

According to the legend, Internet-of-Things (IoT) started in the early 1980s, when a Coke-vending machine at the Carnegie Mellon University was connected to the internet (<https://www.cs.cmu.edu/~coke/>). In these pioneering times, integrating custom hardware into a computer network was a challenge for technical specialists. Nowadays, different IoT standards and protocols facilitate the data telemetry and processing (Ponnusamy and Rajagopalan, 2018).

The IoT platform ThingsBoard supports various telemetry protocols. For the MeteoMex project, HTML was chosen for its simplicity in programming and testing. The correct set-up of a device can be verified by sending data from a computer console. E.g., the following command sends the value 99 of the variable humidity for a device with the token uVCGuzjBqV:

```
curl -v -X POST -d "{\"humidity\":99}"
```

```
187     http://www.meteomex.com:8080/api/v1/uVCGuzjBqV/telemetry
188     --header "Content-Type:application/json"
```

189 Wemos boards also could be connected to other IoT platforms. The integration into Blynk
190 (<https://blynk.io>) and Thinger.io (<https://thinger.io>) was successful. But apart from
191 technical questions, the licensing scheme of IoT platforms is relevant. ThingsBoard ([https://](https://thingsboard.io)
192 thingsboard.io) is licensed under the Apache 2.0 license ([https://www.apache.org/licenses/](https://www.apache.org/licenses/LICENSE-2.0)
193 [LICENSE-2.0](https://www.apache.org/licenses/LICENSE-2.0)). I.e., besides being open-source, ThingsBoard offers a free *Community Edition*
194 and allows its employment in commercial applications. ThingsBoard is cross-platform compat-
195 ible and can be installed on Windows, Mac, and Linux ([https://thingsboard.io/docs/user-](https://thingsboard.io/docs/user-guide/install/installation-options/)
196 [guide/install/installation-options/](https://thingsboard.io/docs/user-guide/install/installation-options/)). The system used in this study was installed on
197 Ubuntu 18.04 LTS (<https://ubuntu.com>). The computational capacity of the Virtual-Private-
198 Server, hosted by IONOS (<https://www.ionos.de>), can be adjusted to the IoT server load. How-
199 ever, the installation of a ThingsBoard *Community Edition* IoT server is possible at no software
200 cost.

201 The open-source PostgreSQL (<https://www.postgresql.org>) database server for storing
202 the IoT data has high performance and robustness. Database maintenance and data manip-
203 ulation are possible with system tools and external programs. Exported data can be further
204 analyzed, e.g., with statistics and data mining software, such as R/Rattle ([https://rattle.](https://rattle.togaware.com)
205 [togaware.com](https://rattle.togaware.com)) (Williams, 2011).

206 Transferring data with radio frequency (R.F.) and Bluetooth was tried as well. However,
207 the direct connection of the devices to WiFi networks turned out the technically easiest solu-
208 tion. WiFi networks are ubiquitously available, of fair security, and no additional adaptors are
209 necessary to send collected data to the internet.

210 The ThingsBoard dashboards are visualized on a standard web browser, making it compat-
211 ible with standard personal computers and mobile devices. The web platform also permits the
212 setting-up of data processing pipelines, the *IoT Rule Engine*, and the definition of alarm levels
213 and actions.

214 At the time of writing this manuscript, the IoT server was running for more than 180 days
215 without interruption, demonstrating technical robustness. Although the IoT server was located
216 in Germany, and the sensor units in Mexico, no telemetry data transfer problems were notice-
217 able. Local power cuts or internet failures only affect devices in a particular zone. Since the
218 wireless network settings are saved to the ESP8266 flash memory, the Wemos boards reconnect
219 when rebooting.

220 Thus, the overall infrastructure takes into account the main aspects of an IoT system for agri-
221 culture (Elijah et al., 2018), such as cost, simple and robust technology, localization, scalability,
222 and interoperability. Open licenses of hardware and software, and the use of common stan-
223 dards (WiFi network, HTML telemetry, SQL database) assure a long-term, cost-efficient, and

Figure 6. Monitoring ambient air at the National Institute for Respiratory Diseases, INER, Mexico City, Mexico.

provider-independent service.

Different application examples are presented in the next part.

3.2 Example 1: Weather station for climate and volatile organic compounds

Climatic conditions and air pollution directly affect human health and welfare. Therefore, public monitoring data inform the citizens about possibly hazardous levels of contamination.

Figure 6 shows the recording of climate and total volatile organic compounds (tVOC) of a MeteoMex aeria device installed outdoor at the *National Institute of Respiratory Diseases*, INER, Mexico City, Mexico (<http://iner.salud.gob.mx/>). The apparatus is installed next to an aerobiology station for the continuous monitoring of pollen and microbial spores.

The readings show a daily tVOC peak at about 8 a.m., which could be caused, for example, by the morning traffic. Sensitive persons should avoid physical activities in periods of increased air contamination. Widely distributed public sampling stations could provide more localized data for warning people about possible health risks. The information also could motivate to reduce contaminating activities in affected areas.

The climate parameters temperature, humidity, and pressure, which are simultaneously recorded, also could be used to estimate the daily global solar radiation using a neuronal net-

Figure 7. Monitoring the air and soil parameters in a domestic greenhouse.

work model (Jimenez et al., 2016).

3.3 Example 2: Greenhouse monitoring (air and soil)

For the optimal growth of plants, adequate air and soil conditions are essential. The conductivity and the dielectric properties of soil depend on its composition, structure, moisture, and salinity (SREENIVAS et al., 1995; Malicki and Walczak, 1999; Wang and Schmugge, 1980). Those can be easily measured, and it was shown that soil electrical conductivity measurements correlate with Local yield (Grisso et al., 2005).

The MeteoMex terra device uses either conductive or capacitive probes to estimate the soil moisture. The capacitive probes are protected against corrosion and, therefore, preferable. Since the analogous measurement only provides an integer value between 0 and 1024, the signal needs to be calibrated. **Figure 7** shows on the left side, the air data, and on the right side, the soil data, which are measured hourly in a domestic greenhouse with automated irrigation. The capacitive soil moisture sensor was calibrated to 0-100% with purified water. The actual sensor readings range between 110-124%, which reflects the dielectric properties of soil.

The average soil temperature of about 22 °C is ~8 K lower than the air temperature, demonstrating the heat capacity and temperature buffer properties of the soil. Besides, the temperature variations during the day are ~15 K for air and ~7 K in the soil.

Figure 8. Monitoring the air conditioning of a high-performance computing server room.

The low average barometric pressure of 80,360 Pa is consistent with the theoretical value of 80,572 Pa, which was calculated for an ambient temperature of 30 °C and an altitude of 1,990 m above sea level (<https://www.mide.com/air-pressure-at-altitude-calculator>).

As the temperature peak at about 12 a.m. with the following decline indicates, the measuring point is only for a short period of day exposed to direct sunlight. Temperature and solar radiation profiles have a direct effect on plant growth. Therefore, *micro-climate engineering*, e.g., by planting shading trees, could become a common practice in future agriculture (Trilnick et al., 2018).

The well-being of farm animals also depends on climate conditions. Temperature and humidity measurements in the barn demonstrated that the heat stress of dairy cattle in Canada was underestimated when using data from meteorological stations. Therefore, reading environmental data in the barn is recommended to determine the actual conditions the cows are exposed (Shock et al., 2016).

The economic sensors and the open IoT platform enable numerous applications in *agriculture 4.0*, *smart farming*, and *urban greening* (Madushanki et al., 2019).

3.4 Example 3: High-performance computing room monitoring (air conditioning)

Delicate equipment such as scientific instruments and high-precision machines require controlled ambient conditions. Overheating or condensation could result in serious device damages. **Figure 8** shows the monitoring of a high-performance computing server room at the *National Laboratory of Genomics for Biodiversity*, Cinvestav Irapuato, Mexico (<https://langebio>).

Figure 9. Monitoring tank filling level and turbidity in a domestic wastewater plant.

cinvestav.mx). The charts demonstrate a tight temperature control with an average temperature of 20.45 °C and less than 1.5 K variation.

The constant monitoring of ambient conditions also helps to detect potentials for energy savings, such as changing the settings of an air conditioning system at night, or during periods of inactivity.

3.5 Example 4: Domestic Wastewater plant

Using treated wastewater for irrigation saves sweet water reserves in dry areas. **Figure 9** shows the block chart of a domestic wastewater treatment plant. The *activated sludge process* for reducing organic soluble solids by microbes requires aeration. This aeration step and the pumping for filtration and irrigation require electric energy. The *food-energy-water nexus* describes the strong interconnection between these resources (D’Odorico et al., 2018).

The presented facility uses photovoltaic energy. For saving electricity, the aeration is not operated continuously, but only during the daytime, and in half-hour intervals. The quality of the treated water needs to be monitored to avoid either over-purification (wasting energy) or insufficient purification (clogging filters). In addition, the irrigation scheme has to be adjusted to the generation of treated water. Unused treated water passes through an overflow-pipe to the public sewer and is lost for irrigation.

The MeteoMex WasteWater prototype (**Fig. 3 and 10**) has two sensors: An analog Arduino turbidity sensor for measuring total suspended solids (TSS), and an ultrasonic distance sensor for estimating the tank filling. The Wemos board and the sensors are located inside the wastewater treatment plant, which is built from ferroconcrete. Thus, a direct WiFi connection to the wireless network is not possible. Thus, a Wemos D1 mini Pro board with an external antenna

Figure 10. Installation of the MeteoMex WasteWater prototype in the domestic wastewater plant. A) Connection of the sensors to the custom-built Wemos shield, B) the turbidity sensor is stuck into a piece of styrofoam for floating, C) protection of the Wemos board against rainwater by a plastic beaker, and external antenna, D) control board for wastewater treatment and irrigation; the power supply with blue light provides the energy for the Wemos board, E) outside view of the wastewater plant.

Figure 11. Monitoring tank filling level and turbidity in a domestic waste water plant. Raw sensor data were processed by the Wemos ESP8266 processor to remove noise.

299 was used.

300 The data of both sensors are noisy (**Fig. 11**). Air bubbles and particles can create spikes in the
 301 turbidity measurements. Scattering and sometimes erratic readings of the ultrasonic distance
 302 sensor are also common and need to be addressed in the data processing. Two methods to filter
 303 noisy signal data are presented here.

304 **3.5.1 Chopping off turbidity spikes**

305 In the case of the turbidity sensor, spikes, i.e., individual values with high apparent intensity,
 306 should be removed. This was done using a circular buffer, which was set-up in the variable
 307 declaration section of the Arduino program:

```
308 // Circular buffer set-up
309 //<https://github.com/rlogiacco/CircularBuffer>
310 #include <CircularBuffer.h>
311
312 CircularBuffer<float,10> turbbuffer;
313 // circular buffer capacity for turbidity is 10
```

314 In the program loop, the minimum value of the last ten readings is determined:

```
315 //Turbidity
316 int turbSensor = analogRead(17);
317 float turbpercent = map(turbSensor,1024,0,0,100);
318
319 turbbuffer.push(turbpercent);
320
321 float turbpercentmin = 100;
322 using index_t = decltype(turbbuffer)::index_t;
323 for (index_t i = 0; i < turbbuffer.size(); i++) {
324     if (turbbuffer[i] < turbpercentmin) {
325         turbpercentmin = turbbuffer[i];}
326 }
```

327 The reported turbidity is slightly underestimating the real value, and the measurement is
328 more sluggish than using the raw readings. However, the spikes are removed efficiently, and
329 the filtered data are more robust, which is importing, for example, for setting an automated
330 alarm level.

331 **3.5.2 Kalman filter for tank level readings**

332 Correcting the readings of the ultrasonic sensor is more complex since random deviations can
333 be in both directions. Thus a Kalman-Filter was used for minimizing estimation errors (Kalman,
334 1960; Simon, 2001).

335 The respective Arduino library is included in the variable declaration section:

```
336 // Kalman Filter library
337 //<https://github.com/denyssene/SimpleKalmanFilter>
338 #include <SimpleKalmanFilter.h>
339 SimpleKalmanFilter ultrasonicKalmanFilter(1, 1, 0.01);
```

340 The filling level is calculated from the reading of the ultrasonic sensor SR04 and the tank
341 dimensions (for details see the program in the GitHub repository).

```
342 float fillpercent = 100 * (1-((distance-47.5)/120));
343
344 // apply Kalman filter
345 float fill_estimate = ultrasonicKalmanFilter.updateEstimate(fillpercent);
```

346 Although the maths behind the Kalman filter is not trivial, it could be easily implemented,
347 and the performance of the ESP8266 is sufficient for real-time signal processing.

4 SUSTAINABILITY AND SOCIO-ECONOMIC IMPACT

As for any technology, the possible negative aspects of its adoption need to be discussed. IoT devices consume energy for themselves and for the data transfer and processing infrastructure. Further, their production consumes resources, and at the end of their life-time, they generate electronic waste (<https://what-is-5g.info/>). Additional environmental issues arise when the devices are powered with batteries.

On the other side, the IoT technology can significantly contribute to saving natural resources (see examples above). The energy consumption of the presented domestic wastewater treatment plant (Example 4, section 3.5) is several kWh/day, compared to only some Wh/day of the MeteoMex device. The energy demand of the IoT equipment corresponds to about 0.1% and enables the continuous monitoring and optimization of the plant. Even little improvements in the wastewater treatment and irrigation process that reduce the energy consumption by a few percent justify the environmental and economic cost of the IoT integration.

In other cases, the IoT devices could be mobile and only connected for project-specific tasks, e.g., for determining the day-night temperature profile of a production facility.

Sustainability was a central design goal of the complete platform. The used boards are highly integrated and provide the necessary computation and networking functions with a minimum of material (3 g for a complete Wemos D1 mini board) and energy. WiFi technology and 5 V USB power supplies are globally available, and no special adaptors are necessary.

Importantly, the low cost of the hardware components and the permissive licenses for all parts of the infrastructure - circuit and PCB board design, database, and IoT platform - make the adoption of an IoT system in marginal production sites feasible. Further, weather enthusiasts and environmental activists could form networks for regional and global data collection. The program code can be re-used by the community, e.g., to integrate more sensors and for education.

5 CONCLUSIONS

The MeteoMex project aims towards a community-driven Internet-of-Things (IoT) framework. Despite the use of basic hardware components and free software, the infrastructure reaches professional-grade performance and robustness.

Monitoring the environmental parameters helps to protect natural resources (water and energy), to timely detect health-hazards, and to increase the production of high-quality food. New, data-driven strategies for food production, such as *micro-climate engineering*, *smart farming*, and *precision agriculture* - here summarized as *agriculture 4.0* require highly localized data. Collecting the readings of multiple simple sensors could provide more useful information than high-resolution data from sparse measurement stations. The presented IoT infrastructure is highly

scalable and can process telemetry data from few to thousands of sensor units.

An essential characteristic of this IoT system is the availability of electronic circuit designs and PCB layouts, program codes, and software under open-source licenses. Further, existing infrastructure such as WiFi networks is used to improve the economic and environmental sustainability. The IoT users are not *locked in* within a proprietary technology, but free to choose from multiple vendors, if they need replacement parts or technical service. The comprehensive documentation and the availability of PCB shields for frequently needed set-ups facilitate the do-it-yourself (DIY) assembly of IoT units. Additional sensors can be easily integrated due to the flexible and modular design of hardware and software.

6 ACKNOWLEDGMENTS

I thank the engineers of ThingsBoard for technical advice, and Dr. Cei Abreu (*National Laboratory of Genomics for Biodiversity, UGA/Langebio, Cinvestav Irapuato, Mexico*) and Dr. Josaphat Montero-Vargas (*National Institute for Respiratory Diseases, INER, Mexico City, Mexico*) for providing sensor data. Equipment and material for the study were provided by Kuturabi S.A. de C.V. The funding had no influence on study design, data collection, and interpretation, or the decision to write this article.

7 CONFLICTS OF INTEREST

RW is a shareholder of the company Kuturabi S.A. de C.V.

REFERENCES

- Adejuwon, J. O. and Agundiminegha, Y. G. (2019). Impact of climate variability on cassava yield in the humid forest agro-ecological zone of Nigeria. *Journal of Applied Sciences and Environmental Management*, 23(5):903–908. Number: 5.
- Antony, A. P., Leith, K., Jolley, C., Lu, J., and Sweeney, D. J. (2020). A Review of Practice and Implementation of the Internet of Things (IoT) for Smallholder Agriculture. *Sustainability*, 12(9):3750. Number: 9 Publisher: Multidisciplinary Digital Publishing Institute.
- Beddows, P. A. and Mallon, E. K. (2018). Cave Pearl Data Logger: A Flexible Arduino-Based Logging Platform for Long-Term Monitoring in Harsh Environments. *Sensors*, 18(2):530.
- Bradford, K. J., Dahal, P., Van Asbrouck, J., Kunusoth, K., Bello, P., Thompson, J., and Wu, F. (2018). The dry chain: Reducing postharvest losses and improving food safety in humid climates. *Trends in Food Science & Technology*, 71:84–93.
- Chaudhary, D. D., Nayse, S. P., and Waghmare, L. M. (2011). Application of Wireless Sensor Networks for Greenhouse Parameter Control in Precision Agriculture. *International Journal of Wireless & Mobile Networks (IJWMN)*, 3(1).

- 416 Cohen, A. J., Brauer, M., Burnett, R., Anderson, H. R., Frostad, J., Estep, K., Balakrishnan, K.,
417 Brunekreef, B., Dandona, L., Dandona, R., Feigin, V., Freedman, G., Hubbell, B., Jobling, A.,
418 Kan, H., Knibbs, L., Liu, Y., Martin, R., Morawska, L., Pope, C. A., Shin, H., Straif, K., Shad-
419 dick, G., Thomas, M., van Dingenen, R., van Donkelaar, A., Vos, T., Murray, C. J. L., and
420 Forouzanfar, M. H. (2017). Estimates and 25-year trends of the global burden of disease at-
421 tributable to ambient air pollution: an analysis of data from the Global Burden of Diseases
422 Study 2015. *The Lancet*, 389(10082):1907–1918.
- 423 Corwin, D. L., Lesch, S. M., Shouse, P. J., Soppe, R., and Ayars, J. E. (2003). Ident-
424 ifying Soil Properties that Influence Cotton Yield Using Soil Sampling Directed by
425 Apparent Soil Electrical Conductivity. *Agronomy Journal*, 95(2):352–364. _eprint:
426 <https://access.onlinelibrary.wiley.com/doi/pdf/10.2134/agronj2003.3520>.
- 427 Dell’Angelo, J., Rulli, M. C., and D’Odorico, P. (2018). The Global Water Grabbing Syndrome.
428 *Ecological Economics*, 143:276–285.
- 429 Dickinson, J. L., Shirk, J., Bonter, D., Bonney, R., Crain, R. L., Martin, J., Phillips, T., and
430 Purcell, K. (2012). The current state of citizen science as a tool for ecological research
431 and public engagement. *Frontiers in Ecology and the Environment*, 10(6):291–297. _eprint:
432 <https://esajournals.onlinelibrary.wiley.com/doi/pdf/10.1890/110236>.
- 433 D’Odorico, P., Davis, K. F., Rosa, L., Carr, J. A., Chiarelli, D., Dell’Angelo, J., Gephart,
434 J., MacDonald, G. K., Seekell, D. A., Suweis, S., and Rulli, M. C. (2018). The
435 Global Food-Energy-Water Nexus. *Reviews of Geophysics*, 56(3):456–531. _eprint:
436 <https://agupubs.onlinelibrary.wiley.com/doi/pdf/10.1029/2017RG000591>.
- 437 Dueben, P. D. and Bauer, P. (2018). Challenges and design choices for global weather and cli-
438 mate models based on machine learning. *Geoscientific Model Development*, 11(10):3999–4009.
439 Publisher: Copernicus GmbH.
- 440 D’Amato, G., Holgate, S. T., Pawankar, R., Ledford, D. K., Cecchi, L., Al-Ahmad, M., Al-Enezi,
441 F., Al-Muhsen, S., Ansotegui, I., Baena-Cagnani, C. E., Baker, D. J., Bayram, H., Bergmann,
442 K. C., Boulet, L.-P., Buters, J. T. M., D’Amato, M., Dorsano, S., Douwes, J., Finlay, S. E., Garrasi,
443 D., Gómez, M., Haahtela, T., Halwani, R., Hassani, Y., Mahboub, B., Marks, G., Michelozzi,
444 P., Montagni, M., Nunes, C., Oh, J. J.-W., Popov, T. A., Portnoy, J., Ridolo, E., Rosário, N., Rot-
445 tem, M., Sánchez-Borges, M., Sibanda, E., Sienra-Monge, J. J., Vitale, C., and Annesi-Maesano,
446 I. (2015). Meteorological conditions, climate change, new emerging factors, and asthma and
447 related allergic disorders. A statement of the World Allergy Organization. *World Allergy Or-*
448 *ganization Journal*, 8(1):1–52.
- 449 El-Ansary, D. O. (2017). Effects of Pre-Harvest Deficit and Excess Irrigation Water on Vine

- 450 Water Relations, Productivity and Quality of Crimson Seedless Table Grapes. *Journal of Plant*
451 *Production*, 8(1):83–92. Publisher: Mansoura University, Faculty of Agriculture.
- 452 Elijah, O., Rahman, T. A., Orikumhi, I., Leow, C. Y., and Hindia, M. N. (2018). An Overview
453 of Internet of Things (IoT) and Data Analytics in Agriculture: Benefits and Challenges. *IEEE*
454 *Internet of Things Journal*, 5(5):3758–3773. Conference Name: IEEE Internet of Things Journal.
- 455 Fagerlund, A. J., Iversen, M., Ekeland, A., Moen, C. M., and Aslaksen, P. M. (2019). Blame it on
456 the weather? The association between pain in fibromyalgia, relative humidity, temperature
457 and barometric pressure. *PLoS ONE*, 14(5).
- 458 Fang, L., Clausen, G., and Fanger, P. O. (1999). Impact of Temperature and Humidity on
459 Chemical and Sensory Emissions from Building Materials. *Indoor Air*, 9(3):193–201. _eprint:
460 <https://onlinelibrary.wiley.com/doi/pdf/10.1111/j.1600-0668.1999.t01-1-00006.x>.
- 461 Fechter, J.-O., Englund, F., and Lundin, A. (2006). Association between temperature, relative
462 humidity and concentration of volatile organic compounds from wooden furniture in a model
463 room. *Wood Material Science & Engineering*, 1(2):69–75. Publisher: Taylor & Francis _eprint:
464 <https://doi.org/10.1080/17480270600900551>.
- 465 García-Lara, S., Saucedo Camarillo, N., and Bergvinson, D. J. (2007). *El silo metalico: Manual*
466 *tecnico de fabricacion y manejo*. CIMMYT. bibtex: Garcia-Lara2007d.
- 467 Gibney, E. (2016). ‘Open-hardware’ pioneers push for low-cost lab kit. *Nature News*,
468 531(7593):147. Section: News.
- 469 Grisso, R. D. R. D., Alley, M. M., Holshouser, D. L., and Thomason, W. E. (2005). Precision Farm-
470 ing Tools. Soil Electrical Conductivity. Accepted: 2015-02-12T21:24:44Z Publisher: Virginia
471 Cooperative Extension.
- 472 Haghighat, F. and De Bellis, L. (1998). Material emission rates: Literature review, and the impact
473 of indoor air temperature and relative humidity. *Building and Environment*, 33(5):261–277.
- 474 Hutchinson, C. (2019). *Arid Lands: Today And Tomorrow*. Routledge.
- 475 Jat, R., Singh, V. P., and Kumar, V. (2020). Greenhouse cultivation of fruit crops with special
476 reference to India: An overview. *Journal of Applied and Natural Science*, 12(2):252–260. Number:
477 2.
- 478 Jimenez, V. A., Barrionuevo, A., Will, A., and Rodríguez, S. (2016). Neural Network for Esti-
479 mating Daily Global Solar Radiation Using Temperature, Humidity and Pressure as Unique
480 Climatic Input Variables. *Smart Grid and Renewable Energy*, 07(03):94. Number: 03 Publisher:
481 Scientific Research Publishing.

- 482 Kalman, R. E. (1960). A New Approach to Linear Filtering and Prediction Problems. *Journal of*
483 *Basic Engineering*, 82(1):35–45. Publisher: American Society of Mechanical Engineers Digital
484 Collection.
- 485 King, B. A., Stark, J. C., and Neibling, H. (2020). Potato Irrigation Management. In Stark, J. C.,
486 Thornton, M., and Nolte, P., editors, *Potato Production Systems*, pages 417–446. Springer Inter-
487 national Publishing, Cham.
- 488 Lake Iain R., Jones Natalia R., Agnew Maureen, Goodess Clare M., Giorgi Filippo, Hamaoui-
489 Laguel Lynda, Semenov Mikhail A., Solomon Fabien, Storkey Jonathan, Vautard Robert, and
490 Epstein Michelle M. (2017). Climate Change and Future Pollen Allergy in Europe. *Environ-*
491 *mental Health Perspectives*, 125(3):385–391. Publisher: Environmental Health Perspectives.
- 492 Liu, C.-C., Chen, W.-H., Yuan, C.-S., and Lin, C. (2014). Multivariate analysis of effects of diurnal
493 temperature and seasonal humidity variations by tropical savanna climate on the emissions of
494 anthropogenic volatile organic compounds. *Science of The Total Environment*, 470-471:311–323.
- 495 Luthra, S., Mangla, S. K., Garg, D., and Kumar, A. (2018). Internet of Things (IoT) in Agricul-
496 ture Supply Chain Management: A Developing Country Perspective. In Dwivedi, Y. K., Rana,
497 N. P., Slade, E. L., Shareef, M. A., Clement, M., Simintiras, A. C., and Lal, B., editors, *Emerging*
498 *Markets from a Multidisciplinary Perspective: Challenges, Opportunities and Research Agenda*, Ad-
499 vances in Theory and Practice of Emerging Markets, pages 209–220. Springer International
500 Publishing, Cham.
- 501 Luwesi, C. N., Obando, J. A., and Shisanya, C. A. (2017). The Impact of a Warming Mi-
502 cro-Climate on Muooni Farmers of Kenya. *Agriculture*, 7(3):20. Number: 3 Publisher: Multi-
503 disciplinary Digital Publishing Institute.
- 504 López-Castillo, L. M., Silva-Fernández, S. E., Winkler, R., Bergvinson, D. J., Arnason, J. T., and
505 García-Lara, S. (2018). Postharvest insect resistance in maize. *Journal of Stored Products Research*,
506 77:66–76.
- 507 Madushanki, A. a. R., Halgamuge, M. N., Wirasagoda, W., and Syed, A. (2019). Adoption of
508 the Internet of Things (IoT) in Agriculture and Smart Farming towards Urban Greening: A
509 Review. Publisher: SCIENCE & INFORMATION SAI ORGANIZATION LTD.
- 510 Malicki, M. A. and Walczak, R. T. (1999). Evaluating soil salinity status from bulk electri-
511 cal conductivity and permittivity. *European Journal of Soil Science*, 50(3):505–514. _eprint:
512 <https://onlinelibrary.wiley.com/doi/pdf/10.1046/j.1365-2389.1999.00245.x>.
- 513 Martínez-Jarquín, S., Moreno-Pedraza, A., Guillén-Alonso, H., and Winkler, R. (2016). Template
514 for 3D Printing a Low-Temperature Plasma Probe. *Analytical Chemistry*, 88(14):6976–6980.

- 515 Mercier, S., Villeneuve, S., Mondor, M., and Uysal, I. (2017). Time-Temperature
516 Management Along the Food Cold Chain: A Review of Recent Developments.
517 *Comprehensive Reviews in Food Science and Food Safety*, 16(4):647–667. _eprint:
518 <https://onlinelibrary.wiley.com/doi/pdf/10.1111/1541-4337.12269>.
- 519 Miller-Robbie, L., Ramaswami, A., and Amerasinghe, P. (2017). Wastewater treatment and reuse
520 in urban agriculture: exploring the food, energy, water, and health nexus in Hyderabad, India.
521 *Environmental Research Letters*, 12(7):075005. Publisher: IOP Publishing.
- 522 Milota, M. R. and Lavery, M. R. (2003). Temperature and Humidity Effects on Emissions of
523 Volatile Organic Compounds from Ponderosa Pine Lumber. *Drying Technology*, 21(1):165–174.
524 Publisher: Taylor & Francis _eprint: <https://doi.org/10.1081/DRT-120017289>.
- 525 Monk, S. (2015). *Fritzing for Inventors: Take Your Electronics Project from Prototype to Product*.
526 McGraw-Hill Education TAB, New York; Blacklick, 1 edition.
- 527 Ould Ahmed, B. A., Inoue, M., and Moritani, S. (2010). Effect of saline water irrigation and
528 manure application on the available water content, soil salinity, and growth of wheat. *Agri-
529 cultural Water Management*, 97(1):165–170.
- 530 Patella, V., Florio, G., Magliacane, D., Giuliano, A., Crivellaro, M. A., Di Bartolomeo, D., Gen-
531 ovese, A., Palmieri, M., Postiglione, A., Ridolo, E., Scaletti, C., Ventura, M. T., Zollo, A., and
532 Air Pollution and Climate Change Task Force of the Italian Society of Allergology, A. a. C.
533 I. S. (2018). Urban air pollution and climate change: “The Decalogue: Allergy Safe Tree” for
534 allergic and respiratory diseases care. *Clinical and Molecular Allergy*, 16(1):20.
- 535 Ponnusamy, K. and Rajagopalan, N. (2018). Internet of Things: A Survey on IoT Protocol Stan-
536 dards. In Saeed, K., Chaki, N., Pati, B., Bakshi, S., and Mohapatra, D. P., editors, *Progress in
537 Advanced Computing and Intelligent Engineering*, Advances in Intelligent Systems and Comput-
538 ing, pages 651–663, Singapore. Springer.
- 539 Racah, E., Beckham, C., Maharaj, T., Ebrahimi Kahou, S., Prabhat, M., and Pal, C. (2017). Ex-
540 tremeWeather: A large-scale climate dataset for semi-supervised detection, localization, and
541 understanding of extreme weather events. In Guyon, I., Luxburg, U. V., Bengio, S., Wallach,
542 H., Fergus, R., Vishwanathan, S., and Garnett, R., editors, *Advances in Neural Information Pro-
543 cessing Systems 30*, pages 3402–3413. Curran Associates, Inc.
- 544 Rosas-Román, I., Ovando-Vázquez, C., Moreno-Pedraza, A., Guillén-Alonso, H., and Winkler,
545 R. (2020). Open LabBot and RmsiGUI: Community development kit for sampling automation
546 and ambient imaging. *Microchemical Journal*, 152:104343.
- 547 Scher, S. (2018). Toward Data-Driven Weather and Climate Forecast-
548 ing: Approximating a Simple General Circulation Model With Deep

- Learning. *Geophysical Research Letters*, 45(22):12,616–12,622. _eprint:
https://agupubs.onlinelibrary.wiley.com/doi/pdf/10.1029/2018GL080704.
- She, X., Cong, L., Nie, B., Leng, G., Peng, H., Chen, Y., Zhang, X., Wen, T., Yang, H., and Luo, Y. (2018). Energy-efficient and -economic technologies for air conditioning with vapor compression refrigeration: A comprehensive review. *Applied Energy*, 232:157–186.
- Shock, D. A., LeBlanc, S. J., Leslie, K. E., Hand, K., Godkin, M. A., Coe, J. B., and Kelton, D. F. (2016). Studying the relationship between on-farm environmental conditions and local meteorological station data during the summer. *Journal of Dairy Science*, 99(3):2169–2179.
- Shrivastava, P. and Kumar, R. (2015). Soil salinity: A serious environmental issue and plant growth promoting bacteria as one of the tools for its alleviation. *Saudi Journal of Biological Sciences*, 22(2):123–131.
- Simon, D. (2001). Kalman filtering. *Embedded systems programming*, 14(6):72–79.
- SREENIVAS, K., VENKATARATNAM, L., and RAO, P. V. N. (1995). Dielectric properties of salt-affected soils. *International Journal of Remote Sensing*, 16(4):641–649. Publisher: Taylor & Francis _eprint: https://doi.org/10.1080/01431169508954431.
- Tefera, T., Kanampiu, F., De Groote, H., Hellin, J., Mugo, S., Kimenju, S., Beyene, Y., Boddupalli, P. M., Shiferaw, B., and Banziger, M. (2011). The metal silo: An effective grain storage technology for reducing post-harvest insect and pathogen losses in maize while improving smallholder farmers' food security in developing countries. *Crop Protection*, 30(3):240–245.
- Trilnick, I., Gordon, B., and Zilberman, D. (2018). Micro-Climate Engineering for Climate Change Adaptation in Agriculture.
- Vergine, P., Salerno, C., Libutti, A., Beneduce, L., Gatta, G., Berardi, G., and Pollice, A. (2017). Closing the water cycle in the agro-industrial sector by reusing treated wastewater for irrigation. *Journal of Cleaner Production*, 164:587–596.
- Vermeulen, S. J., Campbell, B. M., and Ingram, J. S. (2012). Climate Change and Food Systems. *Annual Review of Environment and Resources*, 37(1):195–222. _eprint: https://doi.org/10.1146/annurev-environ-020411-130608.
- Villalobos, F. J., Mateos, L., Testi, L., and Fereres, E. (2016). Air Temperature and Humidity. In Villalobos, F. J. and Fereres, E., editors, *Principles of Agronomy for Sustainable Agriculture*, pages 55–67. Springer International Publishing, Cham.
- Wang, J. R. and Schmugge, T. J. (1980). An Empirical Model for the Complex Dielectric Permittivity of Soils as a Function of Water Content. *IEEE Transactions on Geoscience and Remote*

581 *Sensing*, GE-18(4):288–295. Conference Name: IEEE Transactions on Geoscience and Remote
582 Sensing.

583 Wheeler, T. and Braun, J. v. (2013). Climate Change Impacts on Global Food Security. *Science*,
584 341(6145):508–513. Publisher: American Association for the Advancement of Science Section:
585 Review.

586 Williams, G. (2011). *Data Mining with Rattle and R: The Art of Excavating Data for Knowledge*
587 *Discovery (Use R!)*. Springer Science + Business Media, New York, NY, USA, 1st edition.

588 Wolkoff, P. (1998). Impact of air velocity, temperature, humidity, and air on long-term voc
589 emissions from building products. *Atmospheric Environment*, 32(14):2659–2668.

590 Wolkoff, P. and Kjærgaard, S. K. (2007). The dichotomy of relative humidity on indoor air quality.
591 *Environment International*, 33(6):850–857.

592 Yu, D., Qiao, J., and Shi, P. (2018). Spatiotemporal patterns, relationships, and drivers of China’s
593 agricultural ecosystem services from 1980 to 2010: a multiscale analysis. *Landscape Ecology*,
594 33(4):575–595.